



POLI-MASK 287

Sandblast-Film

Product Information

Adhesive PVC film with matt and reflective free surface. Suitable for lettering and spray-mask film for sign-writing on vehicles, board design and exhibition displays.

Lettering on flexible, flat and lightly structured surfaces.

Especially to be emphasised are the following properties:

- Removable, easy peel adhesive with excellent resistance to solvents and PVC plasticizers.
- High final tack even on rough and structured surfaces.
- Ideal flatness under application conditions.
- Stabilized PVC film with high resistance to solvents giving sharply defined edges and no wrinkling.
- Ideal for flatbed plotters.

Technical Data

Carrier:	PVC film, grey, translucent
Adhesive:	Acrylic
Liner:	Silicon paper, white (140g/m ²)
Adhesion [N/cm]:	1,50 +/- 10 %
Thickness [mm]:	0,09 +/- 5 %

Standard Dimensions

1.220 mm x 50 m

1.000 mm x 50 m

20/05/2008

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de

Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.