


# Application Instructions

## EcoPrint – Printable Flock Film for Solvent and Ecosolvent inks



Print and cut

EcoPrint is a flock film on a polyester liner that can be printed with solvent, ecosolvent, and HP latex inks. It has high elasticity and excellent touch. Even large designs can be applied without loss of wearing comfort.

With the help of a computer and a plotter one can quickly, and cost efficiently, produce the smallest runs on

transfers. EcoPrint is primarily processed on so-called hybrid printers which can print and cut. They can, however, be processed on separate machines without any problems.



weed

Before the designs can be transferred the ink should be dry, otherwise the print could potentially smudge. This can take up to an hour depending on the ink used and the ambient conditions.



Transfer design

The cut and weeded designs are ironed on to the textiles for 17-15 seconds at 160-170 °C. Designs that are not connected are

transferred with a strongly adhesive mounting film. After pressing and a short cooling period the mounting film is removed while still warm.



done!

### Suitable Inks

Solvent, EcoSolvent, Latex

### Transfer requirements

Temp.: 160 – 170 °C  
Time: 17 - 15 s  
Pressure: low/medium

### Suitable Textiles

Cotton, Polyester, Blended fabric. Not suitable for nylon and other coated textiles.

### Wash resistance

40 °C wash resistant

### Packaging

50 cm x 10 m  
75 cm x 10 m  
75 cm x 25 m  
150 cm x 25 m

Additional packaging upon request.



The technical specifications rest on extensive tests and technical research. Due to the variety of possible influences during refinement, and use, the specifications should be viewed as reference values. We recommend a suitability test on the original material. A legally binding warranty of specific characteristics cannot be derived from our specifications.