



POLI-TACK 861

Product Information

Transparent Polyester film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability.

The adhesive can be removed without residue even after long periods of usage.

POLI-TACK 861 transfer film is suitable for thermal transfer of heat sealing substrates, i.e. for the transfer of Flock- and Flex-film onto textiles.

Technical Data

Carrier:	PET-film, transparent	
Adhesive:	Acrylic	
Adhesion [N/cm]:	1,00	+/- 10 %
Thickness [mm]:	0,97	+/- 5 %

Standard Dimensions

500 mm x 10 m
500 mm x 25 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

18/10/2017

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.