



POLI-TACK 860

Product Information

Adhesive polyester film (transparent, 100 μ) coated with an acrylic adhesive of high temperature and solvent resistance.

Suitable for the thermal transfer of printed and weeded textile transfers of the range POLI-FLEX PRINTABLES. After the thermal transfer the film can be peeled hot and cold.

Technical Data

Carrier:	PET film, transparent, 100 μ	
Adhesive:	Acrylate, cross-linked	
Adhesion [N/cm]:	0,30	+/- 10 %
Thickness [mm]:	0,12	+/- 5 %

Standard Dimensions

500 mm x 25 m
750 mm x 25 m
1524 mm x 25 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.