



POLI-MASK 2605

Sandblast-Film

Product Information

Self adhesive PVC film with a reflection free, matt surface. The modified medium tack acrylic adhesive can be peeled off without any residues, even after a long application time.

POLI-Mask 2605 can be cut on all CAD/CAM plotters. For transferring the stencil we recommend PT 190 as an Application Tape.

Universally used for all sandblast applications including stone, marble, glass or plastics. The product performs with a high rebound elasticity which shows excellent contour sharpness.

During application the following conditions are taken into consideration:

Injector-technology

Range of pressure: 2-8 bar

Granulation: 150-250 μ

Pressure beam-technology

Range of pressure: 0,5-3,0 bar

Granulation: 150-250 μ

Only mineral abrasives such as dross, quartz sand, korund or glass-pearls should be used. Abrasives like steel shot or gift shot are not suitable.

Technical Data

Carrier:	PVC film, blue, matt
Adhesive:	Acrylic
Liner:	Silicon paper (120g/m ²)
Adhesion [N/cm]:	1,30 +/- 10 %
Thickness [mm]:	0,35 +/- 5 %

Standard Dimensions

1.220 mm x 20 m

20/05/2008

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de

Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.